

EVEREST 6000

ISO 18752

RECOMMENDED FOR:
DEVELOPED TO WITHSTAND VERY DEMANDING CONDITIONS, VERY HIGH PERFORMANCE IN PRESSURE, PULSING AND FLEXING

RACCOMANDATO PER:
SVILUPPATO PER RESISTERE A CONDIZIONI MOLTO IMPEGNATIVE, PRESTAZIONI MOLTO ELEVATE IN PRESSIONE, IMPULSI E FLESSIONE



Features



Code	Hose size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	Inch	mm	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Lb/ft	kg/mt
TSER604	6	1/4"	6,4	0,69	17,50	6000	420	24360	1680	2,36	60	0,38	0,56
TSER606	10	3/8"	9,5	0,79	20,00	6000	420	24360	1680	3,55	90	0,50	0,74
TSER608	12	1/2"	12,8	0,89	22,70	6000	420	24360	1680	4,73	120	0,58	0,87
TSER610	16	5/8"	16,0	1,05	26,60	6000	420	24360	1680	7,09	180	0,81	1,20
TSER612	19	3/4"	19,0	1,23	31,20	6000	420	24360	1680	8,27	210	1,01	1,50
TSER616	25	1"	25,4	1,52	38,60	6000	420	24360	1680	9,85	250	1,48	2,20
TSER620	31	1" 1/4	31,8	1,92	48,80	6000	420	24360	1680	17,53	445	2,55	3,80
TSER624	38	1" 1/2	38,1	2,24	57,00	6000	420	24360	1680	20,88	530	3,23	4,80
TSER632	51	2"	50,8	2,66	67,50	6000	420	24360	1680	25,61	650	4,37	6,50

Everest 6000
3/4" (19 mm)
 ISO 18752
 Flame Resistant MSHA IC-247
 420 Bar / 42,0 MPa
 6000 Psi

MARKING/MARCATURA: TRANSFER TAPE

OPERATING TEMPERATURE RANGE:
- 40°C/+120°C
(-40°F / +250°F)
with peaks of 125°C (257°F)

TUBE:
oil resistant synthetic rubber

REINFORCEMENT:
4 high tensile steel spirals (DN12 -31)
6 high tensile steel spirals (DN 31- 51)

COVER:
special synthetic rubber

TEMPERATURA DI ESERCIZIO:
- 40°C/+120°C
(-40°F / +248°F)
con punte di 125°C (257°F)

SOTTOSTRATO:
gomma sintetica resistente agli oli

RINFORZO:
4 spirali di acciaio ad alto carico (DN12 -31)
6 spirali di acciaio ad lato carico (DN 31- 51)

COPERTURA:
gomma sintetica speciale

TYPE APPROVAL:

MSHA