

[Home](#) / [Search hydraulic hoses](#) / TEKNOJET 2SC 400

CLEANER HOSE

TEKNOJET 2SC 400

EN 1829 - 2



Professional Water Jet Cleaners

Available cover:

Standard Forever



Available cover color:

Blue Grey Red

Operating Temperature Range:
- 10°C/+135°C (14°F to +275°F)
with peak of +150°C (302°F)

Tube:
Hot water, detergent and oil
synthetic rubber

Reinforcement:
2 high tensile steel braids

Cover:
Synthetic rubber with extreme
abrasion resistance

Dimension table - Hydraulic hoses

Cover type

[- Qualsiasi -]

Cover color

[- Qualsiasi -]

[Click to order](#)

Code	D.N.	Hose size	Outside Diameter	Max Working Pressure	Minimum Burst Pressure	Minimum Bend Radius	Peso	Cover Type
TJ2SC04	6	6.4 mm 1/4 "	13.4 mm 0.53 inch	400 bar 5800 psi	1600 bar 23200 psi	75 mm 2.95 inch	0.27 kg/mt 0.18 lb/ft	Standard
TJ2SC04B	6	6.4 mm 1/4 "	13.4 mm 0.53 inch	400 bar 5800 psi	1600 bar 23200 psi	75 mm 2.95 inch	0.27 kg/mt 0.18 lb/ft	Standard
TJ2SC04R	6	6.4 mm 1/4 "	13.4 mm 0.53 inch	400 bar 5800 psi	1600 bar 23200 psi	75 mm 2.95 inch	0.27 kg/mt 0.18 lb/ft	Standard
TJ2SC04G	6	6.4 mm 1/4 "	13.4 mm 0.53 inch	400 bar 5800 psi	1600 bar 23200 psi	75 mm 2.95 inch	0.27 kg/mt 0.18 lb/ft	Standard
TJ2SC05	8	7.9 mm 5/16 "	15.0 mm 0.59 inch	400 bar 5800 psi	1600 bar 23200 psi	85 mm 3.34 inch	0.32 kg/mt 0.22 lb/ft	Standard
TJ2SC05B	8	7.9 mm 5/16 "	15.0 mm 0.59 inch	400 bar 5800 psi	1600 bar 23200 psi	85 mm 3.34 inch	0.32 kg/mt 0.22 lb/ft	Standard
TJ2SC05R	8	7.9 mm 5/16 "	15.0 mm 0.59 inch	400 bar 5800 psi	1600 bar 23200 psi	85 mm 3.34 inch	0.32 kg/mt 0.22 lb/ft	Standard
TJ2SC05G	8	7.9 mm 5/16 "	15.0 mm 0.59 inch	400 bar 5800 psi	1600 bar 23200 psi	85 mm 3.34 inch	0.32 kg/mt 0.22 lb/ft	Standard
TJ2SC06	10	9.5 mm 3/8 "	17.0 mm 0.67 inch	400 bar 5800 psi	1600 bar 23200 psi	90 mm 3.54 inch	0.40 kg/mt 0.27 lb/ft	Standard
TJ2SC06B	10	9.5 mm 3/8 "	17.0 mm 0.67 inch	400 bar 5800 psi	1600 bar 23200 psi	90 mm 3.54 inch	0.40 kg/mt 0.27 lb/ft	Standard
TJ2SC06R	10	9.5 mm 3/8 "	17.0 mm 0.67 inch	400 bar 5800 psi	1600 bar 23200 psi	90 mm 3.54 inch	0.40 kg/mt 0.27 lb/ft	Standard
TJ2SC06G	10	9.5 mm 3/8 "	17.0 mm 0.67 inch	400 bar 5800 psi	1600 bar 23200 psi	90 mm 3.54 inch	0.40 kg/mt 0.27 lb/ft	Standard
TJ2SC08G	12	12.8 mm 1/2 "	20.4 mm 0.80 inch	400 bar 5800 psi	1600 bar 23200 psi	130 mm 5.11 inch	0.54 kg/mt 0.36 lb/ft	Standard
TJ2SC08	12	12.8 mm 1/2 "	20.4 mm 0.80 inch	400 bar 5800 psi	1600 bar 23200 psi	130 mm 5.11 inch	0.54 kg/mt 0.36 lb/ft	Standard
TJ2SC08B	12	12.8 mm 1/2 "	20.4 mm 0.80 inch	400 bar 5800 psi	1600 bar 23200 psi	130 mm 5.11 inch	0.54 kg/mt 0.36 lb/ft	Standard
TJ2SC08R	12	12.8 mm 1/2 "	20.4 mm 0.80 inch	400 bar 5800 psi	1600 bar 23200 psi	130 mm 5.11 inch	0.54 kg/mt 0.36 lb/ft	Standard

Prodotti

Gamma prodotti
Ricerca raccordi a pressare
Ricerca adattatori
Ricerca tubi idraulici

Documentazione

Documenti tecnici
Certificazioni

Contatti

Recapiti e mappe
Richiesta di assistenza tecnica e reclami
Richiesta certificato di conformità all'ordine
Richiesta di partnership commerciale
Lavora con noi

